

2,500 kVA — Oil-immersed distribution

In-stock reference OT-2500-21 · Ex-stock

Transformer from Protrafo stock, available for purchase or rental. The nameplate data below are taken from the unit itself; price on request.

TECHNICAL SPECIFICATION

Unit parameters

Reference	OT-2500-21
Type	Oil-immersed distribution
Rated power	2,500 kVA
Primary voltage	21 kV
Secondary voltage	800 V
Cooling	ONAN
Vector group	Dyn5
Impedance (uk)	6.05 %
Availability	Ex-stock
Available for	Purchase or rental
Price	On request
In stock	1 unit available

NAMEPLATE

Nameplate data

Manufacturer	IEO Transformatoren BV, Breda
Year of manufacture	2023
Phases · frequency	3 · 50 Hz
HV voltage	21000 V
Tap positions (5)	19950 ... 22050 V ($\pm 2 \times 2,5 \%$)
LV voltage	800 V
Rated current HV	68.7 A
Rated current LV	1804 A
Insulation level	LI 125 kV
Temperature rise oil / winding	60 / 65 K
Short-circuit impedance (uk)	6.05 %
Insulating liquid	Nynas Nytro Libra · IEC 60296
Liquid type	Mineral oil
Oil weight	1010 kg
Active part weight	3140 kg
Conductor material HV / LV	Al / Al
Earth screen	Yes
PCB-free	Yes, ex works

Values as stated on the nameplate of this unit.

To reserve this transformer or request an offer, contact us and quote the reference above. Availability changes daily.