

<b>General Specifications</b>			
Transformer type			Oil immersed, Hermetically sealed
Installation			Outdoor
Applicable standarts			IEC 60076
Rated power	(ONAN)	kVA	630
High voltage		V	15000
High voltage tapplings (no load)		kV	+ 2 x 2,5 % , - 2 x 2,5 %
Low voltage (no load)		V	420
High voltage insulation level	(U <sub>m</sub> / U <sub>AC</sub> / U <sub>LI</sub> )	kV	17,5 / 38 / 95
Low voltage insulation level	(U <sub>m</sub> / U <sub>AC</sub> / U <sub>LI</sub> )	kV	1,1 / 3 / --
Frequency		Hz	50
Vector group			Dyn11
Number of phases			3
Max. ambient temperature		°C	40
Max. temperature rise (winding / oil)		°C	65 / 60
Max. altitude above sea level		m	1000
Permissible short circuit duration		s	2
<b>Guaranteed Values</b>			
Impedance voltage(75°C)	± 10 % tolerance	%	4
No load losses	± 0 % tolerance	W	540
Load losses(75°C)	± 0 % tolerance	W	4600
<b>Structural Specifications</b>			
High voltage winding conductor material			Al
Low voltage winding conductor material			Al
Oil type			Inhibited Mineral Transformer Oil
<b>Dimensions and Weight</b>			
Length / Width / Height		mm	1710 / 980 / 1730
Total weight		kg	3060
Weight of active part		kg	2020
Weight of oil		kg	680
<b>Connection Terminals</b>			
High voltage			Plug-in Bushings 24 kV 250A x 3
Low voltage			Porcelain Bushings 1kV 1000A x 4
<b>Accessories</b>			
Hermetical Protection Relay			
Off - circuit tap changer			
Lifting lugs			
Pressure relief valve			
Oil filling & drain valves			
* All weights and dimensions are given approximately.			
** Tolerances for the losses and impedance are according to IEC 60076-1			